

Upgraded Contamination Control Protects Data Center Uptime



Why is protecting equipment from air and surface contamination important?

An average minute of data center downtime costs \$8,851¹



of data center managers say their last outage was **preventable**.²



of data center failures are caused by **human error**.³



of data managers believe their last outage of \$1M or more could have been prevented with better **processes, management, or configuration**.³

Your data center isn't average. Upgraded procedures protect on three fronts:

1 Control All Entry Points to Keep Contamination Out:

- ☐ Use double sets of doors
- ☐ Seal the envelope
- ☐ Install entryway matting
- ☐ Restrict operations and materials
- Keep out particles, cut energy cost of cooled air loss
- All assembly or unpacking should happen in staging areas outside the data center

2 Control What's Already Made It Inside:

- ☐ Empty all trash receptacles daily
- ☐ Target all entryway floors for vacuuming
- ☐ Use strict SOPs for tools and cleaning patterns
- ☐ Subfloor plenums and drop ceilings decontaminated
- ☐ Monitor humidity levels
- Micro and macroscopic protocols
- Use cleaning products approved for data center equipment

3 Control the Equipment that Controls Your Environment:

- ☐ Change cooling system filters on schedule
- ☐ Clean ducts and airways on schedule to avoid buildup
- ☐ Maintain systems mechanically
- Stop particles created by wear and tear



Particular Problems:

Air pollution | Dirt and dust | Electrostatic dust | Ferrous metal particles | Fibers | Human hair | Lint | Packing materials | Pollen | Salt (sea or deicing) | Skin particles | Zinc (and tin) whiskers

All your operations and equipment affect each other.



Particulates in HVAC systems can increase cooling energy costs.

EPA recommends removing contaminants to reduce energy use.⁴



Airborne gases can also lead to corrosion and failures.

ASHRAE recommends data centers monitor for corrosion rates.⁵



Particles and build up can interfere with critical equipment and cause failures.

ASHRAE recommends ISO Class 8 clean room requirements for data centers.⁵

We Develop Targeted SOPs for Data Center Contamination Control
Talk to the Team that Optimizes Operations for Uptime and Efficiency

866.448.4979 | [ABM.com/Mission-Critical](https://abm.com/Mission-Critical)

©2025 ABM Industries Inc. | All rights reserved. | ABM-08260-1019

Sources:

1: https://www.vertiv.com/globalassets/documents/reports/2016-cost-of-data-center-outages-11-11_51190_1.pdf 2: <https://www.datacenterknowledge.com/uptime/lessons-years-data-center-outages-focus-fundamentals>
3: <https://journal.uptimeinstitute.com/how-to-avoid-outages-try-harder/> 4: https://www.epa.gov/sites/production/files/2015-01/documents/energy_executive_summary.pdf
5: <https://www.ashrae.org/File%20Library/Technical%20Resources/Publication%20Errata%20and%20Updates/2011-Gaseous-and-Particulate-Guidelines.pdf>